


Future-cast:  
Timber construction and  
whole life carbon





2024 / Structural Timber Conference  
London

**Chris Gaze**

# Whole life carbon




# Carbon in-use: FHS Case Studies (see Future Homes Hub)



# Project 80: Design Specification

	Type 1	Type 2	Type 3
External wall U-value (W/m <sup>2</sup> K)	0.13	0.13	0.13
Air permeability (m <sup>3</sup> /h/m <sup>2</sup> )	1.5	1.5	5
Y-value	0.028	0.0274	0.028
Ventilation	MVHR	MVHR	IEF
	As built: 2.43 & 2.46	As built: 2.58 & 2.98	As built: 4.51 – 4.99 (8 homes)





# Project 80: Construction and costs


- Fully filled 150mm cavities
  - Clean mortar from behind bricks
  - Placing solid insulation
  - Detailing around windows
  - Xtratherm insulation 382% additional cost (average £2900 per house)
- Type 1 & 2 non-permeable blocks
  - Average £1200 per house
- Type 1 & 2 polymer spray
  - No one else can work in the houses
  - Average £2900 per house
- Improvements will be made
  - Trades will improve
  - Costs will reduce




# Future Homes Hub Details (see guides)

U-value	Insulation	Structure	Description (dims in mm)	Dim	
0.19 15% timber fraction	Mineral wool $\lambda=0.032$	Lightweight blk	140mm full fill cavity	28	370
		Timber Frame	Int cavity, low-e BM, 140 stud		342
	PIR $\lambda=0.022$	Aircrete	75mm insulation & 50mm cavity	38	355
		Timber Frame	Low-e BM, 120 PIR in 140 stud		317
0.18 masonry/ 0.17 timber frame 15% timber fraction	Mineral wool $\lambda=0.032$	Aircrete	150mm full fill cavity	13	380
		Timber Frame	Int cavity, low-e BM, 25 PIR over boarding, 140 stud		367
	PIR $\lambda=0.022$	Aircrete	85mm insulation & 50mm cavity	2	365
		Timber Frame	Int cavity, low-e BM, 25 PIR over boarding, 90 PIR in 140 stud		367
0.15 15% timber fraction	Mineral wool $\lambda=0.032$	Aircrete	185mm full fill cavity	33	415
		Timber Frame	Int cavity, low-e BM, 40 PIR over boarding, 140 stud		382
	PIR $\lambda=0.022$	Aircrete	85 insulation in cavity & 50 clear. 35 on plasterboard	23	390
		Timber Frame	Int cavity low-e BM, 25 PIR over boarding, 90 PIR in 140 stud		367

# Whole Life Carbon vs Embodied carbon




# Whole Life Carbon for 1 m<sup>3</sup> of timber (indicative only)







# Whole Life Carbon for 1 m<sup>3</sup> of timber (indicative only)



# Upfront carbon only (ignore biogenic carbon)




# Time Value of Carbon over 60 years



# Whole Life Carbon Calculation is coming

- WLCA is coming
  - Significant lobbying (including Part Z campaign)
- Government to seek views – could be this year
- The RICS Professional Standard main calculation “cancels out” the advantages of sequestration
- Benchmark yourselves – perhaps via the Future Homes Hub
- Look to reduce carbon wherever you find it



# Conclusion: Carbon Headlines

- Good whole carbon results
  - Not to be taken for granted
- Compact walls for a given U-value
- Airtight (if you want it to be)
- A dry process which quickly produces a weathertight shell





